





- Based on Leeb (HLD), converted to Vickers (HV), Brinell (HB), Rockwell (HRC and HRB),
  Shore (HS) and tensile strength (MPa)

  Memory of 99 measurement values for browsing
- Set measurement times (1~9) to have average value
- Connected with printer via bluetooth
- Automatic power off, according to ASTM A 956



hardness test block D (included)



wireless printer (optional)

## **SPECIFICATION**

Min. reading	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa		
Accuracy	±6HLD (when HLD=800)		
Display	Leeb (HLD), converted hardness, material, impact direction, test times, average value, date		
Output	bluetooth		
Applicable workpiece	minimum weight	5kg	
		2kg (on solid support)	
		0.1kg (coupled on plate)	
	minimum thickness: 5mm		
	minimum radius of curved surface: 30mm		
	maximum roughness (Ra): 1.6µm		
Power supply	3×AAA batteries		
Dimension	150×84×28mm		
Weight	200g		

## STANDARD DELIVERY

Main unit	1 pc
Impact device D	1 pc
Hardness test block D	1 pc
Small support ring	1 pc
Cleaning brush	1 pc

## OPTIONAL ACCESSORY

OI HONAL ACCECCON		
Wireless printer	ISH-DS-PRINTER	
Couplant	ISH-COUPLANT	
Support rings		
Hardness test block D	HDT-B-HLD3	