

AUTOMATIC ROCKWELL HARDNESS TESTER

CODE ISH-MR150**



SPECIFICATION

Hardness scale	HRA, HRB, HRC, HRD, HRF, HRG
Preliminary test force	98N
Test force	588N, 980N, 1471N
Display	analogue
Stage elevation	manual
Load control	automatic (load/dwell/unload)
Load dwell time	1~99 second
Min. reading	0.5HR
Max. workpiece height	170mm
Max. workpiece depth	165mm (from the center of indenter)
Power supply	220V, 50/60Hz **
Dimension	520×160×700mm
Weight	60kg

** Add “-U” on code No. when power supply is 110V, 50/60Hz

STANDARD DELIVERY

Main unit	1 pc
Ø60mm flat anvil	1 pc
Ø150mm flat anvil	1 pc
V-type anvil	1 pc
Diamond indenter	1 pc
Ø1.5875mm carbide ball indenter	1 pc
Hardness test block HRB88~100	1 pc
Hardness test block HRC60~70	1 pc
Hardness test block HRC20~30	1 pc
Anti-dust cover	1 pc



Ø60mm flat anvil
(included)




Ø150mm flat anvil
(included)



V-type anvil
(included) for
cylinders with
diameter Ø4~60mm



small V-type anvil
(optional) for
cylinders with
diameter Ø2~4mm



OPTIONAL ACCESSORY

Hardness test block HRB88~100	HDT-B-HRB
Hardness test block HRC60~70	HDT-B-HRC3
Hardness test block HRC20~30	HDT-B-HRC1
Small V-type anvil	ISH-SMALLANVIL